

Master Infrared Ceiling Receiver

Part No. **NC302RXC**



Overview

- A ceiling-mountable infrared receiver that will accept Standard & Emergency calls from compatible 800 Series infrared transmitters.
- Can receive line-of-sight infrared signals from around 10m away (dependent on physical conditions and environmental factors).
- Red reassurance LED confirms a call has been made.
- Requires a separate remote reset point such as our NC802DB button reset or NC899IRR keyswitch reset point for cancelling calls.
- Mounts on a standard UK 25mm single gang flush or surface back box.



More Information

Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Red Reassurance LED (lit constant for Standard calls, intermittently for Emergency calls).
Controls	None,
Connections	SIG (Signal); -Ve (Negative); +Ve (Positive); IR (Slave Infrared Input). SIG, MOM and RES are not used.
Onboard 6.35mm Remote Jack Socket	No.
Onboard Infrared Receiver	Yes. Will generate a Standard or Emergency Call when triggered by a compatible 800 Series infrared transmitter.
Product dimensions (mm)	87 W x 87 H x 24 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Black UV stable polycarbonate.



IP Rating IP41.
Weight 62g.
Operating conditions/temperature -5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom