

## Emergency Call Point, Button Reset c/w Remote Socket

Part No. **NC802DEB-1/2**



### Overview

- An attractively designed button-operated call/reset point capable of generating Standard and Emergency calls on an 800 Series Call System.
- Includes a 6.35mm jack plug socket for the connection of an optional tail call lead, pressure mat or other ancillary calling device.
- Red reassurance LED confirms a call has been made.
- Onboard reset button cancels Standard and Emergency calls made from the NC802DEB-1/2 **and** Standard calls made from other devices wired on the same zone (such as ceiling pull units in Ensuite areas).
- Mounts on a standard UK 25mm single gang flush or surface back box.



### More Information

### Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Red Reassurance LED (lit constant for Standard calls, intermittently for Emergency calls).
Controls	Call button (generates Standard calls); Alert button (generates Emergency calls); Reset button (cancels Standard or Emergency calls from the NC802DEB-1/2 and Standard calls from devices wired on th
Connections	SIG (Signal); -Ve (Negative); +Ve (Positive).
Onboard 6.35mm Remote Jack Socket	Yes. For optional tail call leads, floor pressure mats, air switches etc.
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 32 D mm. Mounts on a UK 25mm single gang back box.



Construction & finish	Plastic.
IP Rating	IP20.
Weight	64g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E [sales@c-tec.co.uk](mailto:sales@c-tec.co.uk)  
F 01942 829867 W [www.c-tec.com](http://www.c-tec.com)



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom