

## Isolatable Monitoring Point, Button Reset

Part No. **NC894DKB**



### Overview

- A keyswitch-isolatable monitoring point c/w magnetic door contacts for use with C-TEC's 800 Series Call System.
- Can be used to monitor any device with a normally open or normally closed switch.
- Triggers a Standard call when activated
- Typical uses include monitoring fire exits, drug cupboards, store rooms, etc.
- Isolation keyswitch temporarily turns off the device's monitoring function when in the ISOLATED position.



- Red reassurance LED illuminates when a call is made.
- Includes a RESET button for cancelling calls.
- Mounts on a standard UK 25mm single gang flush or surface back box.



## More Information

## Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Red Reassurance LED (lit constant for Standard calls).
Controls	Isolation keyswitch (switches monitoring off when ISOLATED); Reset button (cancels Standard calls made from the monitoring point and from devices wired on the same Zone).
Connections	SIG (Signal); RC (Signal); -Ve (Negative); SW- (Switched Negative); NO (normally open connection); NC (normally closed connection); T (trigger connection). PLK1 link for n/o or n/c operation.
Onboard 6.35mm Remote Jack Socket	No.
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 35 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	84g
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom