

SC-21-0200-0001-99

SmartCell Dual Smoke/Heat Detector

Overview

The SmartCell Dual Smoke / Heat Detector is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include dual smoke and/or heat detection, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Compact profile
- Flexible detection; smoke and/or heat
- Unique design
- Inbuilt locking mechanism

SC-21-0200-0001-99

SmartCell Dual Smoke/Heat Detector

Technical specifications

General

Wireless frequency 868 MHz

Electrical

Batteries 3 x ER14505M lithium thionyl chloride batteries (Fanso or Titus)

Detection

Sensitivity Smoke: Normal, Normal+AVF. Heat: 58 °C, static (A2S), 58 °C rate of rise (A2R), 72 °C static (BS), 72 °C rate of rise (BR)

Physical

Physical dimensions 110 x 58 mm (Ø x D)

Net weight 0.2 kg

Colour White

Mounting type Ceiling mount

Environmental

Operating temperature -10 to +55°C

Storage temperature -10 to +30°C (with batteries)
-10 to +55°C (without batteries)

Relative humidity 95% noncondensing max.

Environment Indoor

Regulatory

Compliance CE

Certification CPR

Standards EN54-5
EN54-7
EN54-13
EN54-25



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 10:30