

SC-33-0220-0001-99

SmartCell White Sounder and Ceiling-Beacon (VAD White Flash)

Overview

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-33-0220-0001-99

SmartCell White Sounder and Ceiling-Beacon (VAD White Flash)

Technical specifications

General

| | |
|--------------------|---------|
| Wireless frequency | 868 MHz |
|--------------------|---------|

Electrical

| | |
|-----------|--|
| Batteries | 3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus) |
|-----------|--|

Sounder

| | |
|--------------|----------------------|
| Output level | 92 dB(A) at 1 m max. |
|--------------|----------------------|

| | |
|-------------------------|-------------|
| Output level adjustment | High or low |
|-------------------------|-------------|

| | |
|------------------|----|
| Selectable tones | 32 |
|------------------|----|

VAD

| | |
|--------|-------------|
| Colour | white flash |
|--------|-------------|

| | |
|--------|--------|
| Rating | C-3-12 |
|--------|--------|

| | |
|-----------------|-----------------------------------|
| Flash frequency | 0.5 Hz (1 flash, every 2 seconds) |
|-----------------|-----------------------------------|

Physical

| | |
|---------------------|---------------------|
| Physical dimensions | 110 x 79 mm (Ø x D) |
|---------------------|---------------------|

| | |
|------------|--------|
| Net weight | 0.2 kg |
|------------|--------|

| | |
|--------|-------|
| Colour | White |
|--------|-------|

| | |
|---------------|---------------|
| Mounting type | Ceiling mount |
|---------------|---------------|

| | |
|-------------------|---------|
| Mounting position | Ceiling |
|-------------------|---------|

Environmental

| | |
|-----------------------|--------------|
| Operating temperature | -10 to +55°C |
|-----------------------|--------------|

| | |
|---------------------|---|
| Storage temperature | -10 to +30°C (with batteries) -10 to +55°C (without batteries) |
|---------------------|---|

| | |
|-------------------|------------------------|
| Relative humidity | 95% noncondensing max. |
|-------------------|------------------------|

| | |
|-------------|--------|
| Environment | Indoor |
|-------------|--------|

| | |
|-----------|-------|
| IP rating | IP21C |
|-----------|-------|

Regulatory

| | |
|------------|----|
| Compliancy | CE |
|------------|----|

| | |
|---------------|-----|
| Certification | CPR |
|---------------|-----|

| | |
|-----------|---|
| Standards | EN54-3 EN54-13 EN54-23 EN54-25 |
|-----------|---|



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 10:31