





The ViLX-ACP Ancillary Cancel Plate is fully compatible with the Lexicomm EVC range of equipment and the standalone Assist Call range.

**Compact Design** 

BS 8300-2:2018 "Acknowledge" Feature

Blue "Halo"

- Flush or surface mounting
- Braille enhanced Cancel Button
- **Stainless Steel finish**

## **Overview**

The ViLX-ACP Ancillary Cancel Plate is used where additional cancel buttons are required. The Assist Call emergency assistance alarm allows for 2 x standard cancel plates wired on a dedicated circuit, this is generally sufficient for most applications. However, in an accessible bedroom an additional cancel button may be required on the other side of the bed. The cancel plate should be mounted at between 800mm to 1000mm.

The Ancillary Cancel plate should only be used as an additional cancel plate alongside a standard point since it does not have any audible or visible indication. Generally 2 x Ancillary Cancel plates can be added to a standard dedicated Assist Call ViLX-ACA or ViLX-ACB circuit (Please check with Vox Ignis Technical).

## **Technical Specification**

DETAILS	VILX-ACP
PHYSICAL	
Height	86mm
Width	86mm
Depth	22mm
Weight	120 g
Material	Stainless Steel/ Acrylic
Finish	Brushed
PART NUMBERS	
Ancillary Cancel Plate	VILX-ACP
RECOMMENDED CABLES	
Туре	PVC or Fire Rated*
Cores	2 core 1mm CSA
Distance	500m from compatible panel/ controller
STANDARDS COMPLIANCE	
EMC	EN 55035:2017+A11:2020
	EN 55032:2015+A1:2020
LVD	EN IEC62368-1:2020 +
	A11:2020
Product Family	BS 5839-9:2021
	BS 8300-2:2018
*If connected to a Refuge Point	



NORTH EAST BUSINESS & INNOVATION CENTRE, UNIT 27, SUNDERLAND SR5 2TA <u>WWW.VOX-IGNIS.COM</u> COMPANY REG NO: 8892407

ALL INFORMATION IS BELIEVED TO BE CORRECT AT TIME OF PRINTING E&OE. VOX IGNIS OPERATE A POLICY OF CONTINUOUS IMPROVEMENT; ALWAYS CONFIRM SPECIFICATION DETAILS BEFORE PURCHASE.