



The ViLX-CLP-56 Assist Call IP56 Weatherproof Mushroom Call button is fully compatible with the Lexicomm EVC range of equipment and the standalone Assist Call range.

- Key Reset
- IP56 ABS Enclosure
- Pool Alarm
- Panic Alarm
- Highly Visible

Overview

The ViLX-CLP-56 can provide a simple solution for applications such as Pool Alarms and Panic Buttons in fact any application requiring a mushroom call button.

It is wired on a dedicated line but an over door plate can be wired on the same circuit to provide audible and visual indication if required. A cancel button is not used due to the key reset, due to its operation the acknowledgement feature is not compatible with this product.

For simplicity, all wiring is a standard two core cable, the wiring order of the plates is not fixed and therefore can be wired in any order to give total flexibility, several ViLX-CLP-56 can be wired in the circuit.

There are 20mm cable entries on the top and bottom and a cable entry at the rear via a cut out.

Technical Specification

DETAILS	ViLX-CLP-56
PHYSICAL	
Height	75mm
Width	80mm
Depth	55mm Including Button 86mm
Weight	190g
Material	ABS
Colour	Yellow & Grey
PART NUMBERS	
Cancel Plate	ViLX-CLP-56
RECOMMENDED CABLES	
Type	PVC or Fire Rated*
Cores	2 core 1mm CSA
Distance	500m from compatible panel/ controller
STANDARDS COMPLIANCE	
EMC	EN 55035:2017+A11:2020 EN 55032:2015+A1:2020
LVD	EN IEC62368-1:2020 + A11:2020
Product Family	BS 5839-9:2021 BS 8300-2:2018
*If connected to a Refuge Point	